

INVESTIGATION ON PROPERTIES OF CONCRETE CASTED WITH TREATED EFFLUENT: A REVIEW

¹S. S. Nibhorkar, ²Anant Warankar, ³Bhushan Dhote, ⁴Rutuja Jane, ⁵Renuka Kale, ⁶Pallavi Shahane, ⁷Megha Khandekar, ⁸Pragati Koge

P.R. Pote (Patil) college of Engineering and Management, Amravati. Sant. Gadgebaba Amravati University - India.

ABSTRACT

Water is a basic element in construction and construction industry required fresh water. Nowadays, we are facing problem related to availability of fresh/potable water. Considering this problem, this research deals with study of the effect of different type of treated waste water on properties of concrete such as compressive strength with respect to potable water. The domestic treated wastewater sample collected from Sewage water treatment plant (STP) in Lalkhadi and Industrial treated wastewater sample from effluent treatment plant (ETP) near Amravati city. Water samples of domestic treated waste water and industrial treated waste water tested in laboratory to calculate impurities of water such as pH, BOD & COD etc. After testing impurities of treated waste water, it is observed that all parameters of treated water are in permissible limit. Concrete cube casted with Industry treated water, domestic treated waste water and potable water for M20 & M25 grade of concrete and compared result. The result indicate that the compressive strength of industrial treated waste water and domestic treated waste water is gradually decreases but within acceptable limit as compare to the potable water the chemical analysis were performed by free chlorine by (starch iodide test) titration method.

Keywords: Potable water, Domestic treated water, Industrial treated water, Compressive strength.

INTRODUCTION

Water is one of the nature's precious gifts, which sustains life on earth. Civilizations over the world have perished depending upon the availability of this vital resource. Water has been worshiped for life nourishing properties in all the scriptures.

About 71% of earth surface is covered with water and the ocean holds about 97% of and all earths' water, remaining 3% is freshwater. This 3% freshwater is categorized as 79% is covered with icecaps and glaciers, 20% is groundwater and remains only 1% surface water. This 1% surface water is categorized as 52% water covered by lakes, river1%, 1% consume by living organism, 38% is soil moisture 8%, 6% atmospheric water vapour. The water covered by lakes and reservoirs is useful for drinking and many other purposes and may

DISTRIBUTION OF WATER ON EARTH



subjected to various losses also

LITERATURE REVIEW

Ramkar A.P. et.al (2016) The effect of different source of treated waste water on properties of concrete i.e. compressive strength, tensile strength and flexural strength of concrete has checked. The treated waste water has been collected from waste water treatment plant situated at shirdi. They have used PTWW (primary treatment waste water) and STWW (secondary treatment waste water) process and also they have checked the chemical properties of collected treated waste water in laboratories. After determining the properties of collected sample from treatment plant they have cast the cubes using M30.

K. Nirmal kumar et.al (2008) investigated that, durability impact of concrete by using recycled wastewater. They used the recycled wastewater from the tannery industry for the construction purpose, so that the shortage in water can be greatly reduced by making some primary treatment. Then the specimens were also casted by adding the concrete admixture with dosages of 0.5%, 1.0%, 1.5%, 2.0% and 2.5%. The specimens were tested for durability properties for 28 days, 90 days and 365 days. By using these cubes and cylinder were casted and tested for its durability (sulphate attack, chloride attack and corrosion impact).

K.S. Al-Jabri et.al (2011) carried out study on treated waste water for concrete mix then they have checked which effects are developed on properties of high strength concrete. The sample was collected from three car washing stations in Muscat area. They have cast different types of samples for testing purpose i.e. first six cubes are cast in size 150 x 150 x 150, second three cylinders are cast in size 300 x 150 diameter and last three prisms are cast in 100 x 100 x 500 dimension. They have determined the compressive strength, tensile strength and flexural strength at 28 days of curing. And also, compressive strength of cubes checked for 7-day curing. They have concluded that when curing period increases the compressive strength of concrete is also increases using waste water there is no significant difference. It may be also concluded that from this study that the use of waste water produced from car washing stations has negligible effect on the strength of concrete

Asif Rashid sheikh et.al (2016) Main aim of this study is to determine the quality of water which was used for mixing purpose for concrete. They have the waste water collect from waste water treatment plant at Kuwait. They have used M20 grade of concrete. They have concluded that comparison between potable water concrete and treated waste water concrete are giving nearly similar results. [4] P. Rama Mohan Rao carried out the study on treated waste water for preparing concrete mix are suitable or not suitable and also studied which exactly effect is developed on concrete by using treated waste water. They have also checked what exactly happen when waste water used in reinforcement concrete. They have concluded that treated waste water is suitable for construction activity without compromising strength of concrete.

P. Rama Mohan Rao et.al (2014) carried out the study on treated waste water for preparing concrete mix are suitable or not suitable and also studied which exactly effect are developed on concrete by using treated waste water. They have also checked what exactly happen when waste water used in reinforcement concrete. They have concluded that treated waste water is suitable for construction activity without compromising strength of concrete.

H. Vijay et.al (2014) mainly focused on the reuse of treated waste water effluent in place of potable water in plain concrete. They have also studied the effect of physic-chemical characteristics of this non fresh water on concrete. They were used water sample from four source which are treated domestic sewage water, service station water (garage), Dairy waste water and potable water. After sample collecting they were analyzed all sample for pH, total dissolved solids, chloride, hardness, alkalinity, and sulfates. This study concluded that use of treated

effluents auto service station (garage) water and dairy wastewater has no noticeable side effect on the strength of concrete.

Himashu Sharma *et.al* (2015) carried out study on effect of alkaline substance present in mixing and curing water on the compressive strength of concrete is assessed under the laboratory conditions. They have used two type of grade for mixing purpose i.e. M25 and M30. The concrete mix prepared with additional two concentrations of NaOH i.e. 40ml/l and 80ml/l in mixing and curing of water. Compressive strength of concrete was checked for 14, 28 and 90 days. They conclude that compressive strength of concrete decrease with 40ml/l concentration of NaOH as compared to cube cast with normal water when tested for 14, 28 and 90 days. The compressive strength of concrete increase with 80 ml/l concentration of NaOH as compared to cubes cast with normal water when cubes tested at 14 and 28 days but it is decreasing the compressive strength of concrete again when cube tested at 90 days. So, they conclude that some amount of the effected of NaOH on compressive strength of concrete.

Shrilatha *et.al* (2017) carried out study on the primary treated waste water used for concrete mix which was analyzed for chemical properties in laboratories. The waste water sample collected from MYLSANDRA waste water treatment plant. The grade of concrete which they have used is M20. The potable water was replaced with the primary treated waste water in different dilution ratios of 20%, 40% and 100%. They also conclude that the results obtained from treated effluent, compressive strength of concrete is increased by 10.68% till 28 days as compared to potable water.

S.P. Kale *et.al* (2018) This study has evaluated the use of treated waste water for concrete mixing is seen to favourable for strength development. It also seen that reduction in long term strength of concrete including it may possible to use treated waste water in mixing and curing of concrete. However, there is Risk of corrosion of steel reinforcement in concrete.

Mr. K. J. Kucche *et.al* (2015) Impurities present in water are reacting differently with different constituent of cement. These reactions mostly affect the setting time, compressive strength and may also cause straining of concrete surface. All impurities may not have adverse effects on the properties of concrete. Some impurities react such that, net result may be harmless or improve concrete properties. Hence it is difficult to draw a common conclusion for use of water for mixing and curing in concrete. The use of impure water for concrete mixing is seen to favorable for strength development at early ages.

R. A. Taha *et.al* (2010) investigated that, the feasibility of using Ground (brackish) water and Production (oily) water in construction Compared with Tap water. Non fresh water samples were obtained from four P DO (Petroleum Development O man) asset areas. Nine water samples, including controlled potable (tap) water, were analyzed for pH, total dissolved solids (TDS), chloride, hardness, alkalinity, and sulphates. In addition, cement pastes and mortars and plain concrete mixtures were prepared using 100% substitution of potable water. N ine mixtures were prepared and cured for up to one and a half years. Mixtures were tested for initial setting times, compressive strength and flexural strength.

M. Silva and T. R. Naik *et.al* (2010) investigated that unstainable use of resources, such as use of reclaimed water, especially partially processed sewage treatment plant water in concrete. An initial laboratory investigation was conducted samples were collected from the Milwaukee Metropolitan Sewerage District (MMS D) and analyzed the Characteristics of reclaimed wastewater. According to their investigation the compressive strength, mortar cubes with sewage treatment plant water has shown improvement in strength during 3 to 28 days and increased by the duration of 91 days.

KishanLal Jain et.al (2016) This paper reviews the possibility of replacing fresh water with waste water for making concrete. The strength is not affected so much by using waste water as replacement for waste water. From the literature it is seen that, the reaction between waste water and cement affect the workability, compressive strength and flexural strength. The reduced strength is within the acceptable limit. The use of impure water for concrete mixing is reduces the cost of the construction and in this way the process of construction becomes economical.

Ayoub M. Ghrair et.al. (2016) This study has evaluated the use of treated waste water for concrete and mortar production in bench and full scales. The water quality analysis showed that treated waste water is suitable for concrete and mortar production. This study has shown that treated waste water is a potential alternative for fresh water in the concrete industry. Therefore, the current guidelines for wastewater recuse should be revised by the governmental authorities to encourage the use of treated waste water as a substitute for fresh water in concrete production

Abdul Razak et.al (2015) There is a decrease in the workability of concrete using treated waste water whereas gave better workability to concrete. There is no significant difference in the compressive strength value of concrete made using treated waste water and potable water. The tensile strength of concrete made using treated waste water was found to be lesser compared to that of potable water. Considerable construction cost can be reduced by utilizing the treated water for plain cement concrete

U.S Ansari et.al (2016) This study deals with the effect of different type of treated waste water properties of strength of concrete. In that use of concrete mis of M30 the Potable water was fully replaced with the PTWW, STWW & Domestic waste water The consistency, initial e final setting time of cement paste by mixing STWW is within the Is limit. The compressive strength of mouton is in by mixing STWW at the end of 28 days the compressive strength of concrete is increased by mixing stww at the end of 60 days there is no any significant difference in tensile strength & flexure strength is improve by using STWW.

CONCLUSION

Several studies have explored the effects of waste effluents on the properties of cement and concrete. Research conducted by various authors demonstrates that the strength of concrete mixed with waste effluent can be lower compared to samples mixed with fresh water different waste effluents, such as sewage treatment plant effluent, and industrial effluent, have been studied, and their impacts on concrete properties have been assessed. However, some studies have also shown positive effects of waste effluents on concrete properties. For instance, the use of treated domestic sewage effluent resulted in increased compressive strength, attributed to the filling of pores by suspended solids. Overall, the incorporation of waste effluents in cement and concrete production offers potential for sustainable development. However, it is crucial to consider the specific characteristics of the effluents and their effects on the desired properties of cement and concrete. Further research is needed to optimize the use of waste effluents and ensure their compatibility with construction requirements.

REFERENCES

- [1] Ramkar A.P and Ansari U.S (2016), "Effect of Treated Waste Water on Strength of Concrete," IOSR Journal of Mechanical and Civil Engineering (IOSR-JMCE) e-ISSN: 2278-1684, p-ISSN: 2320-334X, Volume 13, Issue 6 Ver. II , PP 41-45.
- [2] K. Nirmalkumar and V.Sivakumar (2008), "A study on the durability impact of concrete by using recycled waste water," Jr. of Industrial Pollution Control 24 pp. 1-8© Enviromedia.

- [3] K. S. Al-Jabri, A. H. Al-Saidy, R.Taha and A.J.Al-Kemyani (2011), "Effect of using waste water on the properties of high strength concrete," *Procedia engineering* 370-376.
- [4] Mr. Asif Rashid Shaikh and Dr. V. M. Inamdar (2016), "Study of Utilization of Waste Water in Concrete," *IOSR Journal of Mechanical and Civil Engineering (IOSR-JMCE)* e-ISSN: 2278-1684, p-ISSN: 2320-334X, Volume 13, Issue 4 Ver. II , PP 105-108.
- [5] P. Rama Mohan Rao, S. M. K. Moinuddin and P. Jagadeesha (2014), "Effect of Treated Waste Water on the Properties of Hardened Concrete," *Int. J. Chem. Sci.*: 12(1), 155-162 ISSN 0972-768X.
- [6] H. Vijay, T.N Shridhara and S.O Ojoawo (2014), "Effects of the Physico-Chemical Characteristics of Treated Wastewater Effluents on Their Reuse in Plain Concrete Works," *Journal of Emerging Trends in Engineering and Applied Sciences (JETEAS)* 5(2): 74-82 © Scholar link Research Institute Journals, (ISSN: 2141-7016).
- [7] Himanshu Sharma, Dr. Hemant Sood, Deepanshu (2015), "Effect of Concentration of Alkaline Water on Strength of Concrete," *International Journal of Civil Engineering*, volume 2, Issue 1 e-ISSN: 1694-2280, p-ISSN: 1694-2396.
- [8] Shrilatha, Rohtih.M , Puneeth.H.C. And Naveen K Khatavkar (2017), "Effect of Primary Treated Waste Water in Concrete Mix," *International Journal of Current Engineering and Scientific Research (Ijcesr)* ISSN (Print): 2393-8374, (Online): 2394-0697, Volume-4, Issue-8,
- [9] Mr. S. P. Kale, Mr. S. M. Shinde, Mr. A. B. Shinde, Mr. N. B. Bodke, Mr. D. N. Dhaware and Prof. C. S. Chavan (2018), "Effect of Treated Waste Water on Properties of Concrete" *Journal of Advances and Scholarly Researches in Allied Education Vol. X*
- [10] Mr. K. J. Kucche, Dr. S. S. Jamkar and Dr. P. A. Sadgir (2015), "Quality of Water for Making Concrete: A Review of Volume 5, Issue 1,1 ISSN 2250-315V, Issue No. 2, (Special Issue), ISSN 2230-7540.
- [11] R. A. Taha (2010), "The feasibility of using Ground (brackish) water and Production (oily) water in construction compared with Tap water", *International Journal of Sustainable Water and Environmental system*, Vol. 1, pp 39-43. E-ISSN NO:2349-0721
- [12] R.A. More and S.K. Dubey (2014), "Study on effect of different types of water on compressive strength of concrete", *International Journal of Research in Engg. And Technology*, pp 40-50.
- [13] F. Adeyemiand (2014), "Experimental investigations on the effect of sea water on the compressive strength of concrete", *International Journal of Engg. Science Invention*, pp 23-31
- [14] R. A. Taha (2010), "The feasibility of using Ground (brackish) water and Production (oily) water in construction compared with Tap water", *International Journal of Sustainable Water and Environmental system*, Vol. 1, pp 39-43.
- [15] M. Silva and T. R. Naik (2010), "Sustainable use of resources", *Second international conference construction material*
- [16] E.W. Gadzama (2015), "Study on the effect of using sugar factory waste water as a mixing water on the properties of normal strength concrete", *International Journal of Science, Environment*. pp 813-825.
- [17] Shetty (2004), *M.S.Concrete technology – Theory and Practice*. 5th ed. S. Chand and Co. Ltd., RamNagar, New Delhi, India.