

THE EFFECTIVENESS OF THE USE OF NONTRADITIONAL AGRICULTURAL ORES IN THE CULTIVATION OF WINTER WHEAT

¹Abdurakhmonov sodikjon Obidovich, ²Abdullaev Ismoiljon Ibrahimjonovich

Doctor of Agricultural Sciences¹, PhD in Agricultural Sciences² Andijan branch of Tashkent State Agrarian University Uzbekistan, Andijan region, Andijan district, Kuygan-yor town, Oliygox street, 1
ismoil_abdullaev@mail.ru

ANNOTATION

In the conditions of typical gray soils of Tashkent region, before sowing of winter wheat under the plow once in three years in addition to the norms of mineral fertilizers $N_{200}P_{140}K_{100}$ ва $N_{150}P_{105}K_{75}$ kg/ha 1,5-3,0-4,5 t per hectare. The effect of irrigation on soil agrophysical properties and plant growth and grain yield was studied for three years in the order of 60–70–60 and 70–80–70% of the soil moisture before irrigation during the period of application, using bentonite mud.

The obtained data show that the pre-irrigation soil moisture is irrigated in the order of 60–70–60% relative to LMFC, in addition to the norms of mineral fertilizers ($N_{200}P_{140}K_{100}$ ва $N_{150}P_{105}K_{75}$ /hec) 1,5–3,0–4,5 t per hectare. Germination of seedlings 18–16 compared to control options when using bentonite silts in the amount of 18–16; 33–28 and 46–44 m²/piece, total number of stems 49,0–81,6; 96,6-99,4; 104,7-108,3 m²/piece, and the number of productive stems is 47,4-76,1; 97,7-100,3; 102,2-107,6 m²/grain was observed, grain yield was 6,9-11,3; 8,8-13,4; It was noted that it was higher than 10,1-14,7 ts/hect.

Pre-irrigation soil moisture is irrigated at 70–80–70% relative to the LFMC, in addition to the norms of mineral fertilizers $N_{200}P_{140}K_{100}$ ва $N_{150}P_{105}K_{75}$ kg/hect, 1,5–3,0–4,5 t per hectare. The number of seedlings germinated per 1 m² in the variants using bentonite mud in the amount of 22–41–50 to 15–36–51 m²/piece compared to the control variant, the total number of stems 44,2–42,4; 55,8-60,8; 86,5-92,3 m²/piece, number of productive stems 47,5-61,2; 60,2-79,6; Found to be higher than 90,0–108,6 m²/unit, 5,6–9,4 per hectare; 8,2-11,9; 10,0-13,6 quintals of additional grain yield was obtained.

Keywords: *typical gray soil, soil volume weight, soil water permeability, mineral fertilizers, bentonite sludge, winter wheat, seedling thickness, total and productive stem, LFMC, grain and straw harvest.*

INTRODUCTION

Wheat grain is one of the most widely consumed food products of the world's population and is the leading crop in terms of area among cereal crops. A report by the United Nations (UN) and the Food and Agriculture Organization (FAO) in October 2019 showed that wheat production in the world is increasing year by year. According to the data, the gross grain yield of wheat in 2016 was 729 million tons, in 2017 - 749 million tons, in 2018 – 760,4 million tons, and in 2018 the gross grain yield of total grain crops was 2658,1 million tons. tons, of which 28,6% was wheat grain, and in 2019 it was 2720 million tons, of which 28,9% was wheat grain, and grain production increased by 65,3 million tons or 2,5% compared to 2018.¹

In the world's leading wheat-growing countries, guidelines have been developed and scientifically based for the use of non-traditional agro-ores in a variety of soil conditions as a supplement to mineral fertilizers. The use of non-traditional agro-ores in the soil as a resource-saving technology has improved the agrophysical and agrochemical properties of the soil, accelerated biological processes in the soil, increased the rate of assimilation of applied mineral fertilizers by plants and, consequently, improved grain quality. It should

¹ <http://www.fao.org/worldfoodsituation/csdb/ru/>

be noted that the development of agro-measures to save water and mineral fertilizers, using non-traditional agro-ores in the production of high-quality grain from winter wheat is a topical issue.

Studies by Russian scientists A.S. Sokolov and UG Distanov [6] have shown that the specificity of bentonite, its physical and chemical properties, the source of micronutrients in terms of composition, which helps the absorption of mineral fertilizers, water and soil while increasing the ion absorption properties, it has a comprehensive effect on increasing soil fertility.

They concluded that reducing the amount of harmful salts in the soil helps to increase physiological processes, as well as increases the plant's resistance to various diseases.

According to A.V. Tsygankov [7], in the conditions of black chestnut soils of Russia, the application of bentonite mud to winter wheat in the amount of 7.5 t/ha, up to 15,1% compared to the control variant of grain yield, 52, Increased to 2%. In addition to these norms of bentonite sludge, when mineral fertilizers were applied at the rates of $N_{60}P_{60}$ and $N_{60}P_{60}K_{60}$ kg/ha, the grain yield was 25,4–26,7% higher than the control variant.²

According to S.Abdurahmanov [4], in the conditions of grazing soils of Surkhandarya region, before sowing of cotton, bentonite mud in the amount of 9000 kg / ha was applied under the autumn plowing, and during the growing season the pre-irrigation soil moisture was 70-70-60% of LFMC with the application of mineral fertilizers $N_{200}P_{140}K_{100}$ and $N_{150}P_{105}K_{75}$ kg/ha, with an additional yield of 4.2–6.3 quintals of cotton per hectare, 820 m³ of water was saved during the season.

From the analysis of the literature we can see that the application of bentonite sludge to the soil has a positive effect on the agrophysical and aquatic physical properties of the soil, resulting in improved plant growth and nutrient uptake, which has been proven by many scientists.

However, no research has been conducted to study the combined effects of bentonite sludge, mineral fertilizer standards and irrigation regimes on the growth, development and grain yield of winter wheat in the conditions of typical gray soils of Tashkent region.

Procedure and method of conducting the experiment

This research was conducted in 2008-2011 at the Experimental Site of the Research Institute of Cotton Breeding, Seed Production and Agrotechnology (PSUEAITI). This area is located in Kibray district of Tashkent region, 7-8 km from the Chirchik river. in the distance, to the right of the Gray Water Canal.

The soil of the PSUEAITI experimental plot is a typical gray soil with ancient irrigation, groundwater depth 18–20 m, medium and heavy sandy, high carbonate, humus content 1.0–1.5%, total nitrogen 0.08–0, 1 percent, phosphorus 0.2–0.3 percent. Due to the high content of saturated cations, biological processes are accelerated.

Prior to the experiment (2008), 0–30 and 30–50 cm of soil were measured in five-point envelopes to determine the nutrient content of the field soil. Initial soil samples were taken from the layers and analyzed. According to the data obtained, the soil is 0–30 cm. The average humus content in the stratum was 0.897%, total nitrogen was 0.090%, and total phosphorus was 0.096%. The humus content in the stratum was 0.782%, total nitrogen 0.068% and total phosphorus 0.063%.

² <http://vak.ed.gov.ru>

Table 1

Early agrochemical properties of experimental field soils (2008)

Points №	Layer of soil, cm.	General figures, %			Active figures, мг/кг.		
		haze	N	P	N-NO ₃	P ₂ O ₅	K ₂ O
Medium	0-30	0,897	0,090	0,096	3,273	21,62	170
	30-50	0,782	0,068	0,063	2,924	18,32	132

The amount of mobile nutrients in the soil is 0-30 and 30-50 cm. The average nitrate nitrogen in the strata was 3,273–2,924 mg / kg, mobile phosphorus was 21.62–18.32 mg/kg, and exchangeable potassium was 170–132 mg / kg, and the analysis of the obtained data showed that the field was poorly supplied with nutrients. The experimental system consisted of 16 variants, placed in 3 iterations, one tier. In the experimental field, the width of the edges is 60 cm, the length of the edges is 100 m. In the experiment, Moskvich variety of winter wheat was planted. The area of each plot is 480 m², of which the area to be taken into account is 240 m². The total area of the experiments is 2.5 hectares.

In the experiment, two different fertilizer rates ((N₂₀₀P₁₄₀K₁₀₀ and N₁₅₀P₁₀₅K₇₅ кг/га kg / ha), two different irrigation regimes for LFMС 70–80–70 and 60–70–60%, and three different types of bentonite sludge from the Bolgali deposit 1.5–3.0–4 , 5 t / ha standards are set.

The purpose of the study: to determine the amount of mineral fertilizers and water requirements of winter wheat in the application of bentonite mud under the driving conditions of typical gray soils of Tashkent region and to assess the impact of non-traditional crops on wheat growth, development and grain yield.

Table 2

Experimental system (2008–2011)

№	Variants	Fertilizer annual amount, kg/ha			Moisture of soil according to LFMC, %.	
		N	P ₂ O ₅	K ₂ O		
1	Without bentonite	200	140	100	60–70–60	70–80–70
2	Without bentonite	150	105	75		
3	1500 kg/ha bentonite	200	140	100		
4	1500 kg/ha bentonite	150	105	75		
5	3000 kg/ha bentonite	200	140	100		
6	3000 kg/ha bentonite	150	105	75		
7	4500 kg/ha bentonite	200	140	100		
8	4500 kg/ha bentonite	150	105	75		

Note: The norms of bentonite mud shown in the experimental system were applied once before driving in the 1st year before planting, and the effect was studied for 3 years.

RESEARCH METHOD

Placement, calculations and observations of field experiments were carried out on the basis of methodical manuals "Methods of agrochemical, agrophysical and microbiological research in polyfiber districts", "Methods of conducting field experiments" (UzPITI). Statistical analysis of the obtained results was performed on the basis of Microsoft Excel program and B.A. Dospekhov's methodical manual and economic efficiency N.A. Baranov's method

FINDINGS FROM THE STUDY

The soil volume weight of the experimental field was measured at the beginning and end of the vegetation, using cylinders with a volume of 500 g/cm³, every 10 cm of soil. 50 cm from the layer. depth samples were taken and determined.

At the beginning of the experiment (2008), samples were taken and analyzed from five points of the field in the envelope method from the plowed (0–30 cm) and plowed (30–50 cm) layers of soil, and an average of 0–30 cm from five points. in the layer, the bulk density of the soil is 1,35 g/cm³, 30–50 cm. layer was 1,40 g/cm³.

By the end of the experiment (2011), when analyzing the volume weight of the soil in the variant section, the pre-irrigation soil moisture was irrigated at 60–70–60% relative to LFMC, and 1,5–3,0–4,5 t/ha in addition to mineral fertilizers N₂₀₀P₁₄₀K₁₀₀ kg/ha. 4.5 t. When applying bentonite mud in the amount of 0–30 cm of soil relative to the control options. in a layer of 0.04–0.05–0.05 g/cm³, 30–50 cm. In addition to the norms of mineral fertilizers N₁₅₀P₁₀₅K₇₅kg / ha, 1.5–3.0–4.5 t per hectare was observed. When using bentonite mud in the amount of 0–30 cm, the volume weight of the soil relative to the control options is 0–30 cm. in the layer 0.02–0.03–0.05 g/cm³, 30–50 cm. and 0,09–0,11–0,11 g/cm³.

In the second irrigation mode (70–80–70% of the LFMC), in addition to the norm of mineral fertilizers N₂₀₀P₁₄₀K₁₀₀ kg / ha, bentonite mud in the amount of 1.5–3.0–4.5 t/ha was applied under the plow, in accordance with the above laws. the bulk density of the soil relative to the control option at the end, 0–30 cm. layer 0.04–0.06–0.08 g/cm³ per hectare, 30–50 cm. 0.05–0.06–0.08 g/cm³ in the stratum, in addition to the norm of mineral fertilizers N₁₅₀P₁₀₅K₇₅ kg/ha, when applying bentonite mud in the amount of 1,5–3,0–4,5 t/ha. 30 cm. in the layer 0,04–0,07–0,08 g/cm³, 30–50 cm. was found to be less dense by 0,03–0,04–0,07 g/cm³.

Table 3
Soil volume weight of the experimental field, g/sm³

№	Variants	according to LFMC, %.	2008- year	
			0–30	30–50
	At the beginning of growing		1,35	1,40
	At the end of growing		2011- year	
1	Without bentonite	60–70–60	1,40	1,46
2	Without bentonite		1,38	1,47
3	1500 kg/ha bentonite		1,36	1,41

4	1500 kg/ha bentonite		1,36	1,38
5	3000 kg/ha bentonite		1,35	1,38
6	3000 kg/ha bentonite		1,35	1,36
7	4500 kg/ha bentonite		1,35	1,36
8	4500 kg/ha bentonite		1,33	1,36
9	Without bentonite		1,44	1,51
10	Without bentonite		1,44	1,49
11	1500 kg/ha bentonite		1,40	1,46
12	1500 kg/ha bentonite	1,40	1,46	
13	3000 kg/ha bentonite	1,38	1,45	
14	3000 kg/ha bentonite	1,37	1,45	
15	4500 kg/ha bentonite	1,36	1,43	
16	4500 kg/ha bentonite	1,36	1,42	

Another agrophysical property of soil is water permeability. The permeability of the soil itself is called the water permeability and its amount is measured by the amount of water that passes through the soil over a period of time (mm. hour or m^3/ha).

Based on this, we analyzed the water permeability of the soil in an envelope method from five points of the field area at the beginning of the 2008 experiment. Accordingly, it was found that the experimental field soaked an average of $870 m^3/ha$ of water for 6 hours.

Towards the end of the experiment (2011), when the water permeability of the soil was determined in the cross section of the options, it was found that the irrigation norms in the experiment also had an effect on the permeability in accordance with the law. However, in the variants where bentonite mud was used, it was observed that the soil water permeability was higher in both irrigation regimes than in the control.

The obtained data show that in addition to the norms of mineral fertilizers $N_{200}P_{140}K_{100}$ and $N_{150}P_{105}K_{75}$ kg/ha, 1.5–3.0–4.5 t. per hectare. bentonite turbidity in the amount of 60–70–60% of the pre-irrigation soil moisture relative to the LFMC in the irrigated variant, the water permeability of the soil in relation to the control variant 10–5; 20–30; 22–30 m^3/ha , pre-irrigation soil moisture 70–70–70% relative to LFMC, and 105–95 in irrigated versions; 107–100; 103–97 m^3/ha was found to absorb a lot of water.

Table 4
Soil water permeability in the experimental field, $m^3/ha/hour$

№	Variants	Order of watering, according to LFMC.	At the end of experiment, during 6 hours
	At the beginning of experiment (2008 year)		870
	At the end of growing		2011-year

1	Without bentonite	60–70–60%	855
2	Without bentonite		860
3	1500 kg/ha bentonite		865
4	1500 kg/ha bentonite		865
5	3000 kg/ha bentonite		875
6	3000 kg/ha bentonite		890
7	4500 kg/ha bentonite		877
8	4500 kg/ha bentonite		890
9	Without bentonite	70–80–70%	760
10	Without bentonite		765
11	1500 kg/ha bentonite		865
12	1500 kg/ha bentonite		860
13	3000 kg/ha bentonite		867
14	3000 kg/ha bentonite		865
15	4500 kg/ha bentonite		863
16	4500 kg/ha bentonite		862

However, it can be concluded from the data obtained that an increase in the number of irrigations leads to an increase in volume weight in the soil and a deterioration in water permeability, in which case the application of bentonite mud had a positive effect on soil volume weight and water permeability.

At the time of irrigation of the experimental options, the threshold was 50 and 25 cm. the amount of water used for irrigation was determined using a Chippoletti water meter with a width.

Analyzing the experimental data, the norms of mineral fertilizers $N_{150}P_{105}K_{75}$ kg/ha were applied, and when the pre-irrigation soil moisture was 60–70–60% relative to the LFMC, the control option was irrigated a total of 3 times during the application period, 0–2–1 in the irrigation system. 1 time (irrigation rate 860 m³/ha), 1 time during sowing (irrigation rate 880 m³/ha), and 1 time during ripening period (irrigation rate 850 m³ / ha), seasonal irrigation rate was 3350 m³ In the case of bentonite mud in the amount of 1500 kg/ha in addition to the norms of mineral fertilizers, a total of 2580 m³/ ha of water was used during the growing season, irrigated 2 times during the growing season, 0–2–0 irrigation system.

In addition to the norms of these mineral fertilizers, even when bentonite sludge is applied at high rates, ie in the amount of 3,0–4,5 t/ha, it is necessary to irrigate a total of 2 times during the growing season in 0–1–1 irrigation system, seasonal water consumption is 2540 m³/ha. and 2500 m³/ha of water consumption.

According to the data obtained, in addition to the norms of mineral fertilizers $N_{150}P_{105}K_{75}$ kg/ha, 1,5–3,0–4,5 t per hectare. It was found that in the variants using bentonite sludge in the amount of 770–810–850 m³/ha compared to the control variant.

In the second irrigation procedure, the same patterns were repeated, with pre-irrigation soil moisture at 70–80–70% relative to LFMC, and 1,5–3,0–4,5 t. per hectare in addition to the norm of mineral fertilizers $N_{150}P_{105}K_{75}$ kg/ha. The variants with bentonite mud were irrigated 3 times during the season in 1–1–1 and 0–2–1 systems, the seasonal irrigation norms were 3660–3500–3400 m³/ha, and 630–790–890 m³/ha more than the control variant. was found to have been saved, and it was observed that the above laws had been proved.

The full germination of wheat sown in the fall depends on many factors, mainly the biological characteristics of the variety, planting times, soil moisture, fertilization with mineral fertilizers, temperature and others.

Data on seedling thickness of winter wheat during the growing season of 2009–2010 show that the effect of mineral fertilizers and bentonite mud norms on germination and seedling thickness of winter wheat was significant among the options.

In particular, pre-irrigation soil moisture is irrigated at 60–70–60% relative to the LFMC, in addition to the norms of mineral fertilizers ($N_{200}P_{140}K_{100}$ and $N_{150}P_{105}K_{75}$ kg/ha) 1,5–3,0–4,5 t. per hectare. when using bentonite muds in the amount of 18–16 compared to the control options; It was found that 33–28 and 46–44 m²/piece of seedlings sprouted a lot.

In the second irrigation regime in the experiment (pre-irrigation soil moisture 70–80–70% relative to LFMC), in addition to the two norms of mineral fertilizers ($N_{200}P_{140}K_{100}$ and $N_{150}P_{105}K_{75}$ kg/ha), 1,5–3,0 per hectare, in addition to the two norms of mineral fertilizers, while maintaining the above regularity 4.5 t. The number of seedlings germinated per 1 m² ranged from 290–309–318 to 276–297–312, while the number of seedlings per hectare increased from 22–41–50 to 15–36–51 m²/unit compared to the control variant. observed.

With the autumn wheat, the period of time until the end of the application period is the viability of the plant. Survival varies depending on several factors: soil-climatic conditions, level of nutrition, planting times and standards, irrigation, biological characteristics of the variety. Data from experiments conducted during the growing season of 2009–2010 also to some extent confirmed the above ideas.

In particular, pre-irrigation soil moisture is irrigated at 60–70–60% relative to the LFMC, in addition to the norms of mineral fertilizers $N_{200}P_{140}K_{100}$ kg/ha 1,5–3,0–4,5 t. per hectare. It was observed that the death of seedlings in the winter with the use of bentonite mud in the amount of 0,6–1,0–1,4% less than the control option.

Irrigated in the same irrigation regime, in addition to the norms of mineral fertilizers $N_{150}P_{105}K_{75}$ kg/ha, 1,5–3,0–4,5 t per hectare. It was noted that the use of bentonite mud in the amount of 1,4–2,5–3,3% less than the control option.

The same pattern was observed in the second irrigation regime (70–80–70% of the LFMC), in addition to the norms of mineral fertilizers $N_{200}P_{140}K_{100}$ kg/ha, 1,5–3,0–4,5 t per hectare. In variants 11–13–15 with the use of bentonite mud in the amount of 0,3–1,4–1,9% compared to the control variant, in addition to the norms of mineral fertilizers $N_{150}P_{105}K_{75}$ kg/ha 1,5–3,0–4,5 per hectare t. In variants 12–14–16, where bentonite mud was applied in the amount of 1,7–3,3–3,9%, it was observed that the loss of seedlings was low.

However, when the actual thickness of seedlings at the end of the application period was studied in terms of variants, it was observed that during the period from collection to the end of the ripening period, seedlings died under the influence of various factors.

According to the data obtained, pre-irrigation soil moisture is irrigated at 60–70–60% relative to LFMC, and in addition to the norm of mineral fertilizers $N_{200}P_{140}K_{100}$ kg/ha, 1,5–3,0–4,5 t. per hectare. By the

end of the application period, the actual seedling thickness was 239–254–267 m²/piece, the number of dead seedlings was 6,1–5,6–5,2%, and the number of seedlings compared to the control variant was 3–5–7 variants. In addition to the norm of mineral fertilizers N₁₅₀P₁₀₅K₇₅ kg/ha, it was observed that the number of dead seedlings was higher by 19–34–47 m²/unit, the amount of dead seedlings was reduced by 0,6–1,1–1,5%, 1,5–3,0–4,5, t. per hectare. By the end of the validity period, the actual seedling thickness was 227–242–258 m² / piece, the number of dead seedlings was 6,5–6,0–5,8%, and the number of seedlings compared to the control was 18– 33–49 m²/unit, and the number of dead seedlings was found to be 0,7–1,2–1,4% lower

Table 5

Effect of bentonite turbidity on experimental winter wheat germination and seedling thickness, 2010

№	The number of sprouted seedlings m ² /piece	The number of seedlings perished in winter, %	The number of seedlings obviated winter, m ² /piece	The number of perished plants from gathering to the end of maturing, %	The number seedlings at the end of, m ² /piece
1	259	8,9	236	6,7	220
2	252	10,7	225	7,2	209
3	277	8,3	254	6,1	239
4	268	9,3	243	6,5	227
5	292	7,9	269	5,6	254
6	280	8,2	257	6,0	242
7	305	7,5	282	5,2	267
8	296	7,4	274	5,8	258
9	268	8,2	246	6,2	231
10	261	10,0	235	6,6	219
11	290	7,9	267	5,6	252
12	276	8,3	253	5,1	240
13	309	6,8	288	4,8	274
14	297	6,7	277	4,5	265
15	318	6,3	298	4,1	286
16	312	6,1	293	4,4	280

The above rules are reflected in the second irrigation regime, when the pre-irrigation soil moisture is 70–80–70% relative to the LFMC, in addition to the norms of mineral fertilizers N₂₀₀P₁₄₀K₁₀₀kg/ha, 1,5–3,0–4,5 t. per hectare. In the variants using bentonite mud, the actual seedling thickness was 252–274–286 m²/piece, the number of dead seedlings was 5,6–4,8–4,1%, and the seedling thickness was 21–43–55 m²/piece higher than the control. seedlings were found to be 0,6–1,4–2,1 percent lower. In addition to the norms of mineral fertilizers

$N_{150}P_{105}K_{75}$ kg/ha, 1,5–3,0–4,5 t. per hectare. In the variants with bentonite mud, the actual seedling thickness was 240–265–280 m^2 /grain, the number of dead seedlings was 5,1–4,5–4,4%, and the seedling thickness was 21–46–61 m^2 /grain higher than the control, the number of dead seedlings decreased by 1,5–2,1–2,2%.

The data obtained show that in addition to the mineral fertilizer standards, in the variants where bentonite mud was used, the effect on seedling germination and actual seedling thickness was found to be significant.

Studies conducted in 2008–2009 and 2010–2011 also obtained data in accordance with the above-mentioned legislation, in addition to mineral fertilizers, 1,5–3,0–4,5 t/ha. It was observed that when bentonite mud was applied, the germination rate of seedlings increased and the mortality of seedlings decreased.

The spike length of the autumn wheat crop, the number of grains in the spike, the weight of the grain in one spike, and the grain weight of 1000 grains are important indicators of wheat yield.

In our experiment from 2008 to 2011, it was observed that the effect of bentonite mud and mineral fertilizers norms and irrigation regimes on the yield elements of winter wheat was specific.

In particular, based on the results of experiments in 2010, pre-irrigation soil moisture was irrigated at 60–70–60% relative to LFMC, mineral fertilizers were applied at the rate of $N_{200}P_{140}K_{100}$ kg/ha, in option 1 (control) the average spike length was 8,6 cm, the number of grains per grain is 38,1 grains, the weight of grain per grain is 1,43 g and the weight of 1000 grains is 37,6 g. 1,5–3,0–4,5 t. per hectare in addition to the norms of mineral fertilizers. In the 3–5–7 variants, where bentonite mud was used in the amount of 8,7–8,9–8,9 cm, the average spike length, respectively. The number of grains per grain is 38,2–38,3–39,1 grains, the weight of grain per grain is 1,48–1,48–1,53 g. and the weight of 1000 grains is 38,6–38,7–39,1 g. showed that.

In the control of variant 2, which was irrigated in this irrigation regime and applied norms of mineral fertilizers $N_{150}P_{105}K_{75}$ kg/ha, the average grain length was 8,3 cm, the number of grains per grain was 38,0 and the weight of grain per grain was 1,39 g. and 1000 grains weighing 36,5 g. 1,5–3,0–4,5 t. per hectare in addition to the norms of these mineral fertilizers. In the case of bentonite mud (4–6–8 variants), the length of the spike is 8,5–8,7–8,8 cm, respectively. The number of grains per grain is 38,1–38,2–38,8 grains, the average grain weight is 1,43–1,45–1,48 g. and the weight of 1000 grains is 37,6–37,9–38,2 g. it was noted that.

Table 6

Effect of bentonite sludge on biometric indicators of autumn wheat, 2010

№	Variants	The length of spike, cm	The number of crops on one spite, piece	The weight of crops on one spite, gr	The weight of 1000 pieces of crops, gr
1	Without bentonite	8,6	38,1	1,43	37,6
2	Without bentonite	8,3	38,0	1,39	36,5
3	1500 kg/ha bentonite	8,7	38,2	1,48	38,6
4	1500 kg/ha bentonite	8,5	38,1	1,43	37,6
5	3000 kg/ha bentonite	8,9	38,3	1,48	38,7
6	3000 kg/ha bentonite	8,7	38,2	1,45	37,9

7	4500 kg/ha bentonite	8,9	39,1	1,53	39,1
8	4500 kg/ha bentonite	8,8	38,8	1,48	38,2
9	Without bentonite	8,8	38,5	1,49	38,7
10	Without bentonite	8,5	38,1	1,41	37,0
11	1500 kg/ha bentonite	9,0	38,7	1,50	38,9
12	1500 kg/ha bentonite	8,9	38,5	1,47	38,1
13	3000 kg/ha bentonite	9,3	38,7	1,52	39,2
14	3000 kg/ha bentonite	9,2	38,5	1,50	39,0
15	4500 kg/ha bentonite	9,5	39,5	1,57	39,6
16	4500 kg/ha bentonite	9,2	39,3	1,54	39,2

In the second irrigation regime (70–80–70% of the LFMC), the same pattern was observed, a spike weighing 1,49 g. and 38,7 g per 1,000 grains. 1,5–3,0–4,5 t. per hectare in addition to the norm of these mineral fertilizers. In variants 11–13–15, where the amount of bentonite mud was used in the amount of 9,0–9,3–9,5 cm. The number of grains in one grain is 38,7–38,7–39,5 grains, the weight of one grain is 1,50–1,52–1,57 g. and 1000 grains weighing 38,9–39,2–39,6 g. These indicators are based on the fact that mineral fertilizers $N_{150}P_{105}K_{75}$ kg/ha used in the norm of control 10–variant, the average length of a spike is 8,5 cm. The number of grains in a grain is 38.1 grains, the weight of a grain is 1,41 g. ni, 1000 pieces of grain weight 37,0 g. 1,5–3,0–4,5 t per hectare in addition to the norm of these mineral fertilizers. In 12–14–16 variants, the length of one spike is 8,9–9,2–9,2 cm, the number of grains per spike is 38,5–38,5–39,3 the weight of one spike is 1,47–1,50–1,54 g. and the weight of 1000 grains was 38,1–39,0–39,2 g. It was noted that.

According to the data obtained, in addition to the norms of mineral fertilizers $N_{200}P_{140}K_{100}$ and $N_{150}P_{105}K_{75}$ kg/ha, 3,0–4,5 t. per hectare. It was observed that the application of bentonite mud, the length of the grain, the number of grains per

Table 7
Irrigation regime, norm of mineral fertilizers and autumn wheat grain and straw of bentonite mud
effect on productivity

№	Variants	Pre-irrigation soil moisture relative to LFMC	Mineral Fertilizer Norm, NPK	Grain yield, ts / ha				Straw yield, ts / ha			
				2009	2010	2011	Total	2009	2010	2011	Total
1	Without bentonite	60–70–60%	200–140–100	48,8	44,6	45,8	46,4	57,6	53,0	53,7	54,8
2	Without bentonite		150–105–75	43,7	40,2	40,5	41,5	51,1	47,3	47,3	48,6

3	1500 kgg/ha bentonite	70-80-70%	200-140-100	58,3	53,3	48,2	53,3	78,9	71,4	65,2	71,8
4	1500 kgg/ha bentonite		150-105-75	57,9	52,9	47,5	52,8	71,6	65,1	58,7	65,1
5	3000 kgg/ha bentonite		200-140-100	59,0	55,7	50,8	55,2	80,0	75,3	68,8	74,7
6	3000 kgg/ha bentonite		150-105-75	58,7	55,4	50,6	54,9	71,8	68,6	62,1	67,5
7	4500 kgg/ha bentonite		200-140-100	60,2	56,9	52,5	56,5	82,9	76,9	70,8	76,9
8	4500 kgg/ha bentonite		150-105-75	60,1	56,6	51,9	56,2	74,5	69,1	62,8	68,8
9	Without bentonite		200-140-100	52,2	48,4	46,1	48,9	62,0	56,4	56,7	58,4
10	Without bentonite		150-105-75	48,9	43,6	42,3	44,9	57,1	51,8	51,5	53,5
11	1500 kgg/ha bentonite	200-140-100	58,6	55,5	49,3	54,5	79,5	74,9	67,9	74,1	
12	1500 kgg/ha bentonite	150-105-75	58,0	55,3	49,7	54,3	71,8	67,9	60,7	66,8	
13	3000 kgg/ha bentonite	200-140-100	60,4	59,0	52,0	57,1	82,3	79,2	70,9	77,5	
14	3000 kgg/ha bentonite	150-105-75	59,8	58,8	51,8	56,8	73,6	72,1	63,1	69,6	
15	4500 kgg/ha bentonite	200-140-100	62,9	60,8	52,9	58,9	84,6	81,6	72,1	79,4	
16	4500 kgg/ha bentonite	150-105-75	62,6	60,5	52,5	58,5	77,0	74,8	64,2	72,0	

grain, the weight of the grain per grain and the weight of 1000 grains were significantly affected.

In the conditions of typical gray soils of Tashkent region, the requirements of winter wheat variety "Moskvich" for bentonite sludge, norms of mineral fertilizers and irrigation procedures were studied.

Accordingly, the pre-irrigation soil moisture was irrigated at 60-70-60% relative to the LFMC, and in the control variant of mineral fertilizers $N_{200}P_{140}K_{100}$ kg/ha, the average grain yield was 46,4 ts/ha in three years, in addition to the norm of mineral fertilizers. 1,5-3,0-4,5 t. per hectare. The average yield of 53,3-55,2-56,5 ts/ha was obtained in three years, respectively, with the use of bentonite mud (3-5-7 variants), with an additional 6,9-8,8-10,1 ts/ha grain yield was obtained. Irrigated in this irrigation regime, it was observed that the control of mineral fertilizers $N_{150}P_{105}K_{75}$ kg/ha yielded an average grain yield of 41,5 ts/ha in three years (43,7-40,2-40,5) from option, which is in line with the standards of these mineral fertilizers. in addition, 1,5-3,0-4,5 t per

hectare. In the variants with the use of bentonite mud (4–6–8), the grain yield was 52,8–54,9–56,2 t/ha, respectively, and 11,3–13,4–14,7 t/ha more than the control. Was found to be a grain crop.

The second irrigation regime was carried out when the pre-irrigation soil moisture was 70–80–70% relative to the LFMC, and mineral fertilizers were applied at the rate of $N_{200}P_{140}K_{100}$ kg/ha. Control variant 9 yielded an average grain yield of 48.9 ts/ha in three years. In addition, 1,5–3,0–4,5 t. per hectare. When using bentonite mud, the grain yield was 54,5–57,1–58,9 ts/ha, respectively, and 5,6–8,2–10,0 ts/ha more than the control variant. In this irrigation procedure, the standard yield of mineral fertilizers $N_{150}P_{105}K_{75}$ kg/ha was obtained from the control variant 10 with an average grain yield of 44,9 t/ha in three years, in addition to the norms of these mineral fertilizers 1,5-3,0-4,5 t/ha. 54,3–56,8–58,5 ts/ha of grain were harvested in three years from the 12–14–16 variants using bentonite mud in the amount of 9,4–11,9–13,6 ts/ha in addition to the control. Yield was obtained.

The data show that the effect of bentonite mud, mineral fertilizer standards and irrigation regimes on the grain yield of winter wheat was significant.

CONCLUSIONS

1. In the typical gray soils of Tashkent region, bentonite mud in the amount of 3,0 t/ha is applied to the plow once every three years. When irrigated, the weight of the soil volume ranges from 0,03–0,05 g / cm³ in the 0–30 cm layer to 0,07–0,08 g/cm³ in the 0–30 cm layer, and on average 0,07 g/cm³ in the 30–50 layer. Decreased to 11 g/cm³, and soil water permeability was found to increase from 30 m³/ha to 100 m³/ha.

2. In addition to the norms of mineral fertilizers, 3,0 t/ha of bentonite mud was applied under the plow. When irrigated in the order of 80-70%, it is possible to save 790 m³/ha of water.

3. When pre-irrigated soil moisture is 60–70–60 and 70–80–70% relative to the LFMC, in addition to the norms of mineral fertilizers $N_{150}P_{105}K_{75}$ kg/ha when applying bentonite mud in the amount of 3,0 t/ha under the drive, an additional 11,9 Grain yield was 9–13.4 ts/ha, and the yield was high, ranging from 21.1–18.9%.

REFERENCES

1. Abdullaev, I. I., Yunusov, O. B., & Kimsanova Kh, A. Bentonite, fertilizers, water and grain yield. *ACADEMICIA An International Multidisciplinary Research Journal*. ISSN, 2249-7137.
2. Abdurakhmonov, S. O., & Abdullaev, I. I. (2020). Bentonite Silt, Effects Of Mineral Fertilizer Norms And Irrigation Regulations On Autumn Wheat Yield. *The American Journal of Agriculture And Biomedical Engineering*. ISSN–2689-1018, 2(8), 73-97.
3. Abdurakhmonov, S. O., Abdullaev, I. I., Abdusalomov, M. I., & Uldashev Kh, K. Bentonite silt and irrigation regulations on autumn wheat yield. *EPRA International Journal of Economic Growth and Environmental Issues-Peer Reviewed Journal*. ISSN, 2321-6247.
4. Abduraxmonov C. "Optimization of water-nutrient regimes of cotton using bentonite sludge in combination with mineral fertilizers" // Collection of scientific articles of the scientific-practical conference "Young scientists - a leading force in improving the science and practice of agriculture." Tashkent – 2008. B. 23–27.
5. Obidovich, A. S., Ibrahimjonovich, A. I., & Jurahonovich, A. S. (2020). Irrigation Procedure And The Effect Of Mineral Fertilizer Norms On Autumn Rye Grain Yield. *PalArch's Journal of Archaeology of Egypt/Egyptology*, 17(7), 9872-9883.
6. Sokolov A.S. Informatsionnye materialy VNTsI sistemnyx issledovaniy AN SSSR. Vyp. 3, 1982. p. 28–29.

7. Tsygankov A.V. "Application of bentonite and mineral fertilizers under winter wheat in dark-chestnut soil" "Abstract of the candidate of agricultural sciences" Persianovskiy – 2011. S. 9–16.
8. Абдуллаев, И. Бентонит лойқаси, маъдан ўғитлар меъёрлари ҳамда суғориш тартибларининг кузги бугдой дон ҳосилдорлигига таъсирини баҳолаш. Авттореферат» Тошкент–2008. Б, 8-14.
9. Абдуллаев, И. И., & Абдурахмонов, С. О. (2018). Бентонитовая глина и урожай зерна. Актуальные проблемы современной науки, (2), 52-56.
10. Абдуллаев, И. И., & Абдурахмонов, С. О. (2018). Влияние бентонитовых глин, норм минеральных удобрений и режима орошения на биометрические показатели озимой пшеницы. In Северный морской путь, водные и сухопутные транспортные коридоры как основа развития Сибири и Арктики в XXI веке (pp. 247-251).
11. Абдуллаев, И. И., & Эрмакова, Ж. М. (2018). ТРЕБОВАНИЯ, ПРЕДЪЯВЛЯЕМЫЕ К ВОДЕ ПРИ ПРИМЕНЕНИИ ГЛИНЫ БЕНТОНИТА ПРИ ПОСЕВЕ ОЗИМОЙ ПШЕНИЦЫ. In Трансформация мирового научно-технического знания (pp. 35-38).
12. Абдуллаев, И. И., Иминов, И. А., & Юлдашев, Р. Т. (2020). Бентонит лойқаси, маъданли ўғитлар меъёрлари ҳамда суғориш тартибларини биргаликда қўллашнинг кузги бугдойдаги маҳсулдорлиги. ЖУРНАЛ АГРО ПРОЦЕССИНГ, 2(6).
13. Абдурахмонов, С. Ж., Абдурахмонов, С. О., & Абдуллаев, И. И. (2020). Влияние норм применения минеральных удобрений и порядка орошения на агрофизические свойства почвы и зерновую урожайность ржи. Актуальные проблемы современной науки, (5), 56-61.
14. Абдурахмонов, С. О., & Абдуллаев, И. И. (2018). КУЗГИ БУГДОЙНИНГ СУГОРИШ МЕЪЁРИГА БЕНТОНИТ ЛОЙКАСИНИНГ ТАЪСИРИ. Irrigatsiya va Melioratsiya, (1), 31-35.
15. Абдурахмонов, С. О., & Абдуллаев, И. И. (2018). ФАКТОРЫ, ВЛИЯЮЩИЕ НА СТРУКТУРУ КОЛОСА ОЗИМОЙ ПШЕНИЦЫ. In Приоритетные направления исследований в рамках естественных и технических наук в XXI веке (pp. 59-62).
16. Абдурахмонов, С. О., & Абдуллаев, И. И. (2021). БЕНТОНИТ, ЎҒИТ, СУВ ВА МАҲСУЛДОРЛИК. DEVELOPMENT ISSUES OF INNOVATIVE ECONOMY IN THE AGRICULTURAL SECTOR, 651-657.
17. Абдурахмонов, С. О., Абдуллаев, И. И., & Акрамова, М. НОРМЫ ОРОШЕНИЯ ОЗИМОЙ ПШЕНИЦЫ ПРИ ПРИМЕНЕНИИ БЕНТОНИТОВЫХ ГЛИН NORMS IRRIGATION OF WINTER WHEAT IN THE APPLICATION OF BENTONITE CLAYS. ББК 65.2 С56, 17.
18. Абдурахмонов, С. О., Абдуллаев, И. И., & Тагаев, А. М. (2021). КУЗГИ ЖАВДАР УРУҒЛАРИНИ ЭКИШ МУДДАТЛАРИ ВА МЕЪЁРЛАРИНИ КЎЧАТ ҚАЛИНЛИГИГА ТАЪСИРИ. DEVELOPMENT ISSUES OF INNOVATIVE ECONOMY IN THE AGRICULTURAL SECTOR, 922-928.